



**Cimar<sup>®</sup>**  
**produzione s.r.l.**

**Via Mecio Gracco 8H/I - 84131 Salerno IT**  
**Tel/Fax +39 089 302418 - [info@cimarproduzione.com](mailto:info@cimarproduzione.com)**  
**[www.cimarproduzione.com](http://www.cimarproduzione.com)**

POLIPRIMER ( Non-film forming primer for PU systems )	technical data sheet
---	----------------------

Revision date 11.04.17

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Nome commerciale: POLIPRIMER (Non-film forming primer for PU systems)  
Produttore : Cimar Produzione Sr.l con stabilimento in Salerno alla via Mecio Gracco 8H/8I.  
Numero telefonico anche per chiamate urgenti: Tel +39 089.302418

#### 2. CHARACTERISTICS AND USES

It is a single-component primer, ready to use, not staining and not filming. Its special formulation allows to create an adhesion bridge over non-porous substrates. Dries in one hour and can be overpainted within 4 hours. Used for tiles, marbles, ceramics, bricks, non-porous concrete, glass, stainless steel, aluminium and metals.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: solvent based liquid  
Solids content = 1%  
Flash point: 12°C (ASTM D93)  
Viscosity at 20°C :3 mPa.s  
VOC content of the product: 860 g/l of ready-to-use product

#### 4. APPLICATION SUPPORT

On metals; remove any traces of grease, oils and soaps by sanding the surface or using phosphating agents.  
On ceramic; clean the surface by abrasion with an abrasive sponge, in limited cases wash with buffered acid and rinse with clean water. Allow to dry perfectly. Always check for rising dampness. It is important to apply the product uniformly and abundantly, evaporating it until the substrate is dry. Cover after one hour maximum, do not exceed four hours, otherwise reapply again.

#### 5. EQUIPMENT

Apply with short hair roller resistant to solvents, brush.

#### 6. CONSUMPTION

Consumption per coat 100-200 gr/sqm.

#### 7. WARNINGS

Do not apply on substrates with rising damp.  
POLIPRIMER contains flammable solvents, follow the instructions of the safety data sheet.  
This product is intended for professional use only.  
For interiors, ventilate well to facilitate solvent migration.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione srl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*