



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - [info@cimarproduzione.com](mailto:info@cimarproduzione.com)  
[www.cimarproduzione.com](http://www.cimarproduzione.com)

PRIMAMANO GOLD (Bituminous Varnish)	technical data sheet
-------------------------------------	----------------------

PRIMAMANO GOLD (Bituminous Varnish)

Revision date 04.01.19

#### 1. IDENTIFICATION OF THE SUBSTANCE / COMPANY

Trade name: PRIMAMANO GOLD (Bituminous paint)  
Additional designation: Bituminous paint based on oxidized bitumen and very fast drying solvents.  
Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.  
Telephone number also for urgent calls: Tel +39 089 302418

#### 2. IDENTIFICATION OF THE SUBSTANCE / COMPANY

Primamano Gold is a high penetration adhesion promoter for bituminous waterproofing materials such as prefabricated membranes, liquid bituminous membranes and hot bitumen. The product consists of bitumen oxidized in solution with solvents of first choice (not regenerated) at very rapid drying and adheres to any surface. The solvents used do not contain even a small percentage of chlorinated solvents. Primamano Gold can also be used as a waterproofing product for vertical masonry surfaces and to protect exposed and buried wooden structures, pipes and metal structures.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Brilliant black liquid  
Specific gravity =  $0.9 \pm 0.05 \text{ kg/dm}^3$   
Dry residue =  $50 \pm 1\%$   
VOC content as required by Legislative Decree No. 161 of 27/05/2006: 750 g/l of product ready for use.  
VOC content of the product: 650 g/l of ready-to-use product

#### 4. DRYING OR HARDENING TO 23°C AND 50% UR

Surface: 10 min  
To the touch: 20 min

#### 5. EQUIPMENT

Apply by brush, roller or airless spray.

#### 6. APPLICATION SUPPORT

Clean and dry surfaces.

#### 7. DILUTION

Ready to use

## 8. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated. Normally it varies from 100-300 gr/sqm depending on the surface.

## 9. INSTRUCTIONS FOR STORAGE

Store dry and well-ventilated place in closed containers away from open flame and heat sources.

Stability in original packages : 12 months

Packing : 18 lt

## 10. AVAILABLE COLORS AND WARNINGS

Black

Do not use the flame on a product that is not perfectly dried.

Flammable product.

Apply the product on perfectly dry substrates.

Carefully clean the surface to be treated, eliminating dust, loose parts, grease, oils and anything else that might affect the anchoring of the product to the support.

Read the safety data sheet carefully before use.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*