



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - info@cimarproduzione.com  
www.cimarproduzione.com

ASFALTO A FREDDO (waterproofing bituminous paste)

technical data sheet

ASFALTO A FREDDO (waterproofing bituminous paste)

revision date 4.10.19

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: ASFALTO A FREDDO (waterproofing bituminous paste)  
Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.  
Telephone number also for urgent calls: Tel +39 089.3024188

#### 2. CHARACTERISTICS AND USES

ASFALTO A FREDDO is a bituminous waterproofing paste for universal use.  
It can be used as a waterproofing product for walls and roofs, for vapour barriers in thermal insulation, for protective painting of masonry to be buried, for waterproofing tanks and reservoirs not intended to contain drinking water.  
It can be used for the anti-damp coating of external walls.  
It is a water-based product.  
Resists waterlogging.  
It can be mixed in all proportions with water, sand and cement.  
Can be used for gluing insulating panels.  
It can be used for grafting in agriculture.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

It is a thixotropic paste, impalpable and dark in colour, dilutable in water.  
It dries quickly forming a glossy film with the characteristic of presenting high impermeability even in the presence of strong water stagnations.  
Specific gravity =  $1.1 \pm 0.05 \text{ kg/dm}^3$   
Dry residue =  $45 \pm 1\%$   
Viscosity at 23°C\* = thixotropic gel  
VOC content as required by Legislative Decree No. 161 of 27/05/2006: 140 g/l of product ready for use.  
VOC content of the product: 5 g/l of ready-to-use product

#### 4. DRYING OR HARDENING TO 23°C AND 50% UR

Surface: 30 '  
To the touch: 2 hours  
Apparent complete: 6 hours

#### 5. EQUIPMENT

Apply by roller, brush or airless spray.

#### 6. APPLICATION SUPPORT

Clean and dry surfaces.

## 7. DILUTION

Ready to use

## 8. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated.

## 9. INSTRUCTIONS FOR STORAGE

Storage temperature: 5°C ÷ 30°C

Stability in original packages : 12 months

Packaging : 5 Kg-10 Kg -18 Kg

## 10. WARNINGS

Avoid applying the product on surfaces where water stagnation or damp surfaces may occur.

Apply the product at higher temperatures +10°C.

Do not apply in case of imminent rain, dew, mist.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione srl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*