



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - info@cimarproduzione.com  
www.cimarproduzione.com

CoverGold (Acrylic Paint)	technical data sheet
---------------------------	----------------------

CoverGold (Acrylic Paint)

Revision date 04.09.19

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: Gold Cover ( Acrylic Paint )  
Additional designation : (Acrylic paint in water emulsion for the protection of bituminous coverings)  
Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.  
Telephone number also for urgent calls: Tel +39 089 302418

#### 2. CHARACTERISTICS AND USES

Cover Gold is a water emulsion paint based on acrylic styrene resins, used to protect waterproofing bituminous membranes from ultraviolet rays. The product is also used with excellent results on concrete. Thanks to its high content of resin and pigments is a product of high coverage and long life.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Medium viscous pigmented liquid  
Specific gravity =  $1.2 \pm 0.05 \text{ kg/dm}^3$   
Dry residue =  $60 \pm 5\%$   
PH = 9,4  
Viscosity at 23°C\* =  $12000 \pm 2000 \text{ cps}$ .  
(with Brookfield viscometer equipped with impeller no. 4 at speed 5 )  
VOC (g/l) 0,60

#### 4. DRYING OR HARDENING TO 23°C AND 50% UR

Surface: 15 '  
To the touch: 20 '  
Full: 1 hour

#### 5. EQUIPMENT

Apply by roller, brush or airless spray.

#### 6. APPLICATION SUPPORT

Clean and dry surfaces. Do not apply on surfaces where water stagnation may occur. Wait for new bitumen-polymer membranes to mature (at least three months) before painting with COVERGOLD, as the outflow of the oils contained in them could cause the product to detach or areas with colour variations.

#### 7. DILUTION AND CONSUMPTION

Dilute to max 10% of water. Consumption depends on the porosity and regularity of the surface to be treated.

#### 8. INSTRUCTIONS FOR STORAGE

Storage temperature:  $5^\circ\text{C} \div 30^\circ\text{C}$   
Stability in original packages : 12 months  
Packaging : 20 kg

## 9. AVAILABLE COLORS

White, red, green and grey, yellow and blue.  
Other colours are available on request (for minimum order of 1000 Kg).

## 10. WARNINGS

Product is frost sensitive  
Apply only on surfaces with regular water flow, do not apply on surfaces subject to water stagnation.  
Do not apply on wet or damp surfaces.  
Do not use for tanks, basements or canals subject to strong water counter-thrust or pressurized water. Apply at temperatures between +5°C and +35°C. Extreme hot and cold conditions during application should be avoided. Do not apply when the temperature may drop below +5°C during the drying of the paint film. Do not apply on very hot substrates as this will over-accelerate the filming process of the paint with negative consequences on the cohesion and adhesion of the product to the substrate.  
Do not apply with high humidity or risk of rain while the film is drying.  
Apply the second coat when the first coat is perfectly dry.  
It is not a walkable product; it may only be stepped on for periodic maintenance.  
After use, clean the tools with water and, if the product has dried, remove it with white spirit.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*