



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - info@cimarproduzione.com  
www.cimarproduzione.com

GHOST (Water-repellent transparent paint)	technical data sheet
---	----------------------

Revision date 04.01.19

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: GHOST ( Transparent varnish)  
Additional designation: Transparent varnish based on vinyl acetates copolymers in solution with organic solvents.  
Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.  
Telephone number also for urgent calls: Tel +39 (0)89 302418

#### 2. CHARACTERISTICS AND USES

GHOST is a solvent-based water repellent for building substrates such as plaster, cement and fibre cement. GHOST has a high penetration power in porous substrates and an excellent resistance to strong alkalis; it achieves a consolidation of the substrate, as well as a uniformity of its absorption, favouring the subsequent application of water-based paints or wall coverings and improves their performance over time. GHOST is used, with excellent results, to inhibit the absorption of living stone and to preserve it over time. It is used to encapsulate eternity. GHOST acts as a primer for the subsequent application of Membrana Gold, which in turn traps the particles of eternity that otherwise break up and are released into the air. The procedure involves one coat of GHOST, followed by two coats of Membrana Gold. The selvedge has been certified for the effectiveness of the encapsulation carried out with the two products.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Low-viscosity liquid  
Specific gravity =  $0.8 \pm 0.05 \text{ kg/dm}^3$   
Dry residue =  $25 \pm 1\%$   
Viscosity at  $23^\circ\text{C}^*$  =  $2000 \pm 1000 \text{ mPa.s}$   
(with Brookfield viscometer equipped with Mod RVT - 20 rpm at  $20^\circ\text{C}$ , impeller no. 5)  
VOC content as required by Legislative Decree No. 161 of 27/05/2006: 750 g/l of product ready for use.  
VOC content of the product: 650 g/l of ready-to-use product

#### 4. DRYING OR HARDENING TO $23^\circ\text{C}$ AND 50% UR

Surface: 15 '  
To the touch: 30".  
Appears complete: 1 hour  
Shooting time: 3 hours

#### 5. EQUIPMENT

Apply by roller, brush or airless spray.

#### 6. APPLICATION SUPPORT

Clean and dry surfaces.

#### 7. DILUTION

Ready to use

## 8. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated.  
Estimated consumption is 200-300 g/m<sup>2</sup> depending on the substrate.

## 9. INSTRUCTIONS FOR STORAGE

The product must be stored in closed containers away from open flames and heat sources.  
Stability in original packages : 12 months  
Packing : 5 lt - 18 lt

## 10. INFORMATION ON EC REGULATORY REGULATION CEE

Symbol : Harmful

R Phrases

R 10 Flammable

R 11 Highly flammable

R 20 Harmful by inhalation

R 36 Irritating to eyes

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness

S phrases:

S 9 Keep only in the original container in a cool, well-ventilated place.

S 13 Keep away from food, drink and animal feedingstuffs.

S 16 Keep away from sources of ignition and fire. Do not smoke

S 23 Do not breathe aerosols

S 51 Use only in well-ventilated areas.

S 24/25 Avoid contact with skin and eyes.

S 26 in case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 29 Do not empty into drains.

S 33 Avoid the accumulation of electrostatic charges

S 36 Wear suitable protective clothing.

S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container and/or label.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*