



Cimar[®]
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT
Tel/Fax +39 089 302418 - info@cimarproduzione.com
www.cimarproduzione.com

PRIMAMANO ECO (Water-Based Bituminous Primer)	technical data sheet
---	----------------------

Revision date 04.01.19

1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: PRIMAMANO ECO (Water-Borne Primer)
Additional designation: Bituminous primer based on bitumen and water.
Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.
Telephone number also for urgent calls: Tel +39 089 302418

2. CHARACTERISTICS AND USES

Primamano Eco is a water emulsion adhesion promoter for bituminous waterproofing materials such as prefabricated membranes, bituminous liquid membranes and hot bitumen with excellent adhesion on all types of surfaces.
The product consists of selected emulsifiable bitumens, water and additives that allow faster drying.

3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Medium viscous dark brown liquid
Specific gravity = $0.8 \pm 0.05 \text{ kg/dm}^3$
VOC content as required by Legislative Decree No. 161 of 27/05/2006: 30 g/l of product ready for use.
VOC content of the product: 1 g/l of ready-to-use product

4. DRYING OR HARDENING TO 23°C AND 50% UR

Surface: 45".
To the touch: 1 hour and 30 ".
Apparent complete: 2 hours and 30 minutes
Shooting time: 4 hours
The drying time varies according to the outside temperature.

5. EQUIPMENT

Apply by brush, brush or airless spray. It is recommended to immerse the tools themselves in the thinner even during use to prevent product residues from drying out and making them unusable. To clean the tools, use diesel fuel or other common thinners (synthetic, white spirit, toluene).

6. APPLICATION SUPPORT

Clean and dry surfaces. Before applying the next layer, check that the product is dry.

7. CONSUMO

Consumption depends on the porosity and regularity of the surface to be treated. Normally varies from: 150-300 g/m².

8. INSTRUCTIONS FOR STORAGE

Storage temperature: 5°C ÷ 30°C Stability in original packages : 12 months Packing : 18 lt

The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione srl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.