



Cimar[®]
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT
Tel/Fax +39 089 302418 - info@cimarproduzione.com
www.cimarproduzione.com

PRIMER (Bituminous primer)

technical data sheet

PRIMER (Bituminous primer)

Revision date 04.01.19

1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: PRIMER (Bituminous primer)

Additional designation: Bituminous primer based on distilled bitumen and quick-drying solvents.

Manufacturer : Cimar Produzione Sr.l with plant in Salerno at via Mecio Gracco 8H/8I.

Telephone number also for urgent calls: Tel +39 089 302418

2. CHARACTERISTICS AND USES

Primer is a high penetration adhesion promoter for bituminous waterproofing materials such as prefabricated membranes, liquid bituminous membranes and hot bitumen. The product consists of bitumen distilled in solution with quick-drying solvents and adheres to every surface.

The solvents used are regenerated products.

Primer can also be used to waterproof vertical masonry surfaces and to protect exposed and buried wooden structures, pipes and metal structures.

3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Brilliant black liquid

Specific gravity = $0.9 \pm 0.05 \text{ kg/dm}^3$

Dry residue = 35%

VOC content as required by Legislative Decree No. 161 of 27/05/2006: 750 g/l of product ready for use.

VOC content of the product: 650 g/l of ready-to-use product

4. DRYING OR HARDENING TO 23°C AND 50% UR

Full: 1 hours

5. EQUIPMENT

Apply by roller, brush or airless spray.

6. APPLICATION SUPPORT

Clean and dry surfaces.

7. DILUTION

Ready to use

8. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated. Normally it varies from 100-300 gr/sqm depending on the surface.

9. INSTRUCTIONS FOR STORAGE

Store in a dry, well-ventilated place in closed containers away from open flame and heat sources.
Stability in original packages : 12 months
Packing : 5 lt - 10 lt - 18 lt

10. AVAILABLE COLORS AND WARNINGS

Black

Do not use the flame on a product that is not perfectly dried.

Flammable product.

Apply the product on perfectly dry substrates.

Carefully clean the surface to be treated, eliminating dust, loose parts, grease, oils and anything else that might affect the anchoring of the product to the support.

Read the safety data sheet carefully before use.

The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.