



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - [info@cimarproduzione.com](mailto:info@cimarproduzione.com)  
[www.cimarproduzione.com](http://www.cimarproduzione.com)

ULTRAGRIP (Adhesion for cement)	technical data sheet
---------------------------------	----------------------

Revision date 04.01.19

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name: ULTRAGRIP (Adhesive for cement)

Manufacturer : Cimar Produzione Surl with plant in Salerno at via Mecio Gracco 8H/8I.

Telephone number also for urgent calls: Tel +39 089 302418

#### 2. CHARACTERISTICS AND USES

Product based on elastic resins in water emulsion and siliceous aggregates. It is used both indoors and outdoors on wooden surfaces, insulating panels, wall paints, bricks, ceramics, bricks, concrete, metal, gypsum and aerated concrete surfaces, to facilitate adhesion to plasters, shavings, repair mortars or pre-mixed coats. Wait about 6/8 hours before applying the second coat; then, the waiting time will be 18/24 hours before proceeding with the overlapping of the next product.

#### 3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: Viscose paste

Specific gravity =  $1.5 \pm 0.02 \text{ kg/dm}^3$

Dry residue =  $66 \pm 1\%$

VOC (g/l) 0,50

#### 4. EQUIPMENT AND APPLICATION

Apply by roller, brush or hairbrush.

Wait 18/24 hours before proceeding with the overlapping of the cementitious mixes.

Do not apply plaster greater than 2 cm.

Clean tools with water.

#### 5. APPLICATION SUPPORT

Clean and dry surfaces. It is a ready-to-use product.

#### 6. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated. It is estimated at approx. 200-300 gr/sqm.

## 7. INSTRUCTIONS FOR STORAGE

Storage temperature: 5°C ÷ 30°C

Stability in original packages : 12 months

Packaging : 5 Kg - 10 Kg-20 Kg

The product is frost sensitive.

## 8. AVAILABLE COLORS

Pink and White

## 9. WARNINGS

The product must be applied in such conditions that its complete drying can be ensured as soon as possible. Therefore, do not apply the product on frozen surfaces, subject to the rigours of the night or near rainy weather. Do not apply the product on substrates subject to hidden moisture. Wait at least 2 hours (in not extreme climatic conditions) before proceeding with the over-application of the cementitious mixes. In the case of application on insulating panels for coats, instead of the plaster mesh, it is recommended to apply a self-adhesive net between the panels. Do not apply plasters with a thickness of more than 2 cm.

*The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and/or ask for the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or delete the articles, and change the data of the products shown in this brochure, without notice, in which case the information contained herein may no longer be valid.*