



Cimar[®]
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT
Tel/Fax +39 089 302418 - info@cimarproduzione.com
www.cimarproduzione.com

UP & DOWN Solvent-based bituminous adhesive

technical data sheet

UP & DOWN (Solvent-based bituminous adhesive)

Revision Date 29.05.19

1. IDENTIFICATION OF THE SUBSTANCE / COMPANY

Trade name: UP & DOWN (Solvent-based bituminous adhesive)
Product: Cimar Production Surl with plant in Salerno at via Mecio Gracco 8H / 8I.
Telephone for urgent calls: Tel +39 089 302418

2. FEATURES AND USES

is a bituminous solvent-based adhesive based on bitumen, solvents, inert fillers, plasticizers and additives, intended for the cold application of polymer-bitumen membranes to the extrados of supports such as concrete, pre-existing membranes, wood.

3. IDENTIFICATION CHARACTERISTICS OF THE LIQUID PRODUCT

Appearance: thixotropic paste
Density = 1.1 ± 0.05 kg / dm³
Dry residue = $80 \pm 1\%$
VOC content as required by legislative decree of 27/05/2006 n ° 161: 750 g / l of product ready for use
VOC content in the product: 600 g / l of product ready for use

4. DRYING AT 23 ° C AND 50% RH

Setting time: 48 h

5. EQUIPMENT

Apply with a notched trowel or long handle rake.
Before application, homogenize the product using a mechanical stirrer.

6. APPLICATION SUPPORT

The support must be dry, clean, free of friable or non-conforming parts, with slopes of less than 5% (for higher slopes integrate the action of UP & DOWN with appropriate mechanical fasteners), with a surface temperature of the supports not exceeding 40 ° C, at an ambient temperature not lower than +5 ° C, in dry climate conditions.

7. APPLICATION

The product is applied to the support in a uniform manner using a long-handled squeegee or, in areas that are not easily accessible, using a short-handled notched trowel. The final setting time varies according to the type of support, the thickness applied, the temperature and the environmental hygrometric conditions..

8. DILUTION

Ready to use

9. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated, approximately 1-1.2 kg / sqm.

10. STORAGE INSTRUCTIONS

Storage temperature: 5 ° C - 30 ° C

Stability in packages: 12 months

Packaging: 18 kg

Warnings

Carefully follow the Safety Rules. Store in rooms away from direct sunlight or heat sources. The dry film is insoluble in water and soluble in solvents, oils, fats. Use common synthetic or nitro thinners to clean the tools

The information contained in this brochure is, to the best of our knowledge, accurate and correct, but any recommendation or suggestion given is without any guarantee, as the conditions of use are not under our direct control. In case of doubt it is always advisable to carry out preliminary tests and / or request the intervention of our technicians. The company Cimar Produzione surl reserves the right to modify, replace and / or cancel the articles, as well as to change the data of the products presented in this brochure without prior notice, in which case the information contained therein may no longer be valid..