

Poliprimer

**NON-PELLICULAR PRIMER
FOR POLYURETHANE COATINGS**

- Specific adhesion promoter of Cimar POLISUPER on supports such as tiles, marble, bricks, ceramics, glass, aluminium and metals.
- Not recommended for use on porous surfaces.

Potenzio

POLYESTER FIBER MESH

- Reinforcement for liquid waterproofing.
- It forms a single body with polyurethane coating.
- Available in rolls of 1 meter (height) x 100 meters (length) and 20 cm (height) x 50 cm (length).

POLi
POLYURETHANE WATERPROOFING

CIMAR PRODUZIONE

Establishment via Mecio Gracco n°8 - 84131 - Salerno (Italy)
Phone and fax: +39 (0)89 302418

www.cimarproduzione.com · info@cimarproduzione.com

Cimar®

POLi G O L D

THE BREATHING POLYURETHANE WATERPROOFING

It is a water-based product, breathable and walkable. It offers great resistance to adverse weather conditions and hot/cold cycle. It has a minimum lifetime of 7 years, without any maintenance. It can be used on any support that must be protected from water, both horizontally and vertically. It favors the natural transpiration on supports such as cement and wood.

Colours: red, yellow, green, white, light blue, grey

Consult the technical data sheet before application

WATERPROOFING BREATHABLE SYSTEM WITH POLIGOLD

STANDARD APPLICATION

- 1 · POLIGOLD diluted to 20% (300 gr/m²)
- 2 · POLIGOLD first coat (0,8 - 1 Kg/m²)
- 3 · POTENZIO fiber mesh
- 4 · POLIGOLD second coat (0,8 - 1 Kg/m²)



WITH UNIPOL-SAI
over 400 m²



POLi S U P E R

THE WATERPROOFING THAT SAVES YOUR TILES

POLISUPER is a solvent-based polyurethane waterproofing solvent, single component and transparent. It creates a film on the support, creating a glossy barrier, waterproof and walkable, easy to clean and wash.

Polisuper can be used on all Cimar liquid membranes to increase resistance and walkability and give colour to the support. Ideal for flooring large commercial surfaces subjected to considerable wear and tear and industrial cleaning. Thanks to the protection of our POLISUPER, the surface will be aesthetically pleasing and protected.

Consult the technical data sheet before application.

WATERPROOFING SYSTEM WITH POLISUPER

STANDARD APPLICATION

- 1 · SUPPORT / TILES
- 2 · POLIPRIMER (500 - 600 gr/m²) in two coats
- 3 · POLISUPER first coat (250 gr/m²)
- 4 · POLISUPER second coat (250 gr/m²)



WITH UNIPOL-SAI
over 400 m²



POLi G H O S T

THE INVISIBLE PROTECTION THAT PERMEATES THE SUPPORT AND PROTECTS THE FLOOR

- Solvent Silicon resin.
- It waterproofs the support, penetrating the joints 'mortar and between the tiles, thus defending it from future infiltrations.
- It prevents the total removal of flooring of balconies, terraces and other floor surfaces exposed to atmospheric agents.
- It is ideal for waterproofing horizontal surfaces, such as ceramics and tiles.
- It eliminates infiltrations.
- It defends the substrate from future infiltrations.
- It's ready to use.
- It's easy to apply.

